

# SBC54OSBIADA



32.25" x 23.75" x 24.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap beer dispenser in stainless steel for outdoor use

### Highlights:

- Weatherproof design holds up in the outdoors
- 32 inch height fits under lower ADA compliant counters
- Commercially listed to NSF-7 standards

### Product Features:

|                                    |   |
|------------------------------------|---|
| ADA compliant height               | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters                        |
| Commercially approved              | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings                             |
| Built-in capable                   | Front-breathing design allows fully recessed installation under counters  |
| Complete tap kit                   | Includes a 5 lb. CO2 tank and regulator, dual tap draft arm, Sankey American tap, connection hardware, and cleaning kit |
| Dual tap system                    | Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs   |
| 304 grade stainless steel exterior | Complete stainless steel construction for easy durability in the outdoors   |
| Factory installed lock             | Front lock located towards the top of the door for convenient access, with 2 keys included                              |
| Professional handle                | Curved towel bar style handle in brushed stainless steel  |
| Adjustable thermostat              | Interior dial thermostat ensures easy temperature management  |

# SBC54OSBIADA Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 32.0" (81 cm)      |
| Height to Hinge Cap        | 32.25" (82 cm)     |
| Width                      | 23.75" (60 cm)     |
| Depth                      | 24.75" (63 cm)     |
| Depth with Handle          | 27.25" (69 cm)     |
| Depth with door at 90°     | 47.0" (119 cm)     |
| Capacity                   | 5.5 cu.ft. (156 L) |
| Defrost Type               | Automatic          |
| Door                       | Stainless Steel    |
| Cabinet                    | Stainless Steel    |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S              |
| Amps                       | 1.2                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 110.0 lbs. (50 kg) |
| Shipping Weight            | 120.0 lbs. (54 kg) |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101069586       |
| Kegeerator                 |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Tap Kit                    | Yes                |
| Height with Tap            | 47.5" (121 cm)     |
| Number of Taps             | 2                  |
| Thermostat Type            | Dial               |
| Interior Light             | Yes                |
| Fan Type                   | Exterior           |
| Refrigerant                | R600a              |
| Refrigerant Amount         | 0.64 oz.           |
| High Side PSI              | 180.0              |
| Low Side PSI               | 80.0               |
| Inter Height               | 26.25" (67 cm)     |
| Interior Width             | 21.0" (53 cm)      |
| Interior Depth             | 17.75" (45 cm)     |
| Compressor Step Height     | 5.5" (14 cm)       |

|                       |               |
|-----------------------|---------------|
| Compressor Step Width | 21.0" (53 cm) |
| Compressor Step Depth | 5.5" (14 cm)  |
| Temperature Range     | 34° to 43°F   |

