

# SBC56GBINKADA



32.25" x 23.38" x 23.5" (H x W x D)

Built-in undercounter ADA height commercially listed beer dispenser with glass door, lock, and black cabinet; no tapping equipment included

### Highlights:

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

### Product Features:

|                                 |  |
|---------------------------------|--|
| ADA compliant height            | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters |
| Commercially approved           | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings      |
| Built-in capable                | Front-breathing design allows fully recessed installation under counters                         |
| Tap kit not included            | Install your own tapping equipment to create a customized beer cooler                            |
| Designed for 1/6 kegs           | Interior can store up to two sixtel kegs   |
| Double pane tempered glass door | Heat resistant design provides clear view to promote impulse buys                                |
| Factory-installed lock          | Keyed lock conveniently located towards the top of the door for added security (2 keys included) |
| Adjustable thermostat           | Interior dial thermostat ensures easy temperature management                                     |
| Automatic defrost               | No-frost operation for minimum user maintenance  |



## SBC56GBINKADA Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 32.0" (81 cm)      |
| Height to Hinge Cap        | 32.25" (82 cm)     |
| Width                      | 23.38" (59 cm)     |
| Depth                      | 23.5" (60 cm)      |
| Depth with Handle          | 24.88" (63 cm)     |
| Depth with door at 90°     | 44.5" (113 cm)     |
| Capacity                   | 5.5 cu.ft. (156 L) |
| Defrost Type               | Automatic          |
| Door                       | Glass              |
| Cabinet                    | Black              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S              |
| Amps                       | 1.8                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 110.0 lbs. (50 kg) |
| Shipping Weight            | 120.0 lbs. (54 kg) |
| Estimated Time to Ship     | 3 to 5 days        |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| Kegeerator                 |                    |
| Door Swing                 | RHD                |
| Reversible                 | Yes                |
| Thermostat Type            | Dial               |
| Interior Light             | Yes                |
| Fan Type                   | Exterior           |
| Refrigerant                | R600a              |
| Refrigerant Amount         | 0.67 oz.           |
| High Side PSI              | 124.0              |
| Low Side PSI               | 30.0               |
| Inter Height               | 26.0" (66 cm)      |
| Interior Width             | 21.0" (53 cm)      |
| Interior Depth             | 18.0" (46 cm)      |
| Compressor Step Height     | 7.0" (18 cm)       |
| Compressor Step Width      | 21.0" (53 cm)      |
| Compressor Step Depth      | 5.5" (14 cm)       |
| Temperature Range          | 34° to 43°F        |

