



SBC56GBICSSADA



32.25" x 23.38" x 23" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap beer dispenser with glass door, lock, and stainless steel wrapped cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

Product Features:

| | |
|---------------------------------|---|
| ADA compliant height | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters |
| Commercially approved | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings |
| Built-in capable | Front-breathing design allows fully recessed installation under counters |
| Complete tap kit | Includes a 5 lb. CO2 tank and regulator, dual tap draft arm, Sankey American tap, connection hardware, and cleaning kit |
| Dual tap system | Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs |
| Double pane tempered glass door | Heat resistant design provides clear view to promote impulse buys |
| Stainless steel wrapped cabinet | Exterior features a wrapped stainless steel finish for lasting durability in busy commercial settings |
| Professional handle | Curved towel bar style handle in brushed stainless steel |
| Factory-installed lock | Keyed lock conveniently located towards the top of the door for added security (2 keys included) |

SBC56GBICSSADA Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 32.0" (81 cm) |
| Height to Hinge Cap | 32.25" (82 cm) |
| Width | 23.38" (59 cm) |
| Depth | 23.0" (58 cm) |
| Depth with Handle | 25.5" (65 cm) |
| Depth with door at 90° | 44.5" (113 cm) |
| Capacity | 5.5 cu.ft. (156 L) |
| Defrost Type | Automatic |
| Door | Glass |
| Cabinet | Stainless Steel |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.8 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 110.0 lbs. (50 kg) |
| Shipping Weight | 120.0 lbs. (54 kg) |
| Estimated Time to Ship | 3 to 5 days |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| Kegeerator | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Height Adjustable | 47.5 |
| Tap Kit | Yes |
| Number of Taps | 2 |
| Thermostat Type | Dial |
| Interior Light | Yes |
| Fan Type | Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 0.67 oz. |
| High Side PSI | 124.0 |
| Low Side PSI | 30.0 |
| Inter Height | 26.0" (66 cm) |
| Interior Width | 21.0" (53 cm) |
| Interior Depth | 18.0" (46 cm) |
| Compressor Step Height | 7.0" (18 cm) |

| | |
|-----------------------|---------------|
| Compressor Step Width | 21.0" (53 cm) |
| Compressor Step Depth | 5.5" (14 cm) |
| Temperature Range | 34° to 43°F |

