

# FS30LMED



24.63" x 18.5" x 17.75" (H x W x D)

Compact manual defrost all-freezer for medical/general purpose use, with alarm, hospital grade cord, external thermometer and lock

## Highlights:

Designed for general purpose use in medical and scientific facilities

External NIST calibrated temperature readout

High/low temperature alarm warns of fluctuations outside the specified temperature range

## Product Features:

Compact dimensions	Sized for easy use on top of counters
Manual defrost	Static cooling system for improved temperature stability
Temperature alarm	High/low temperature alarm audibly warns when interior is out of set range
NIST calibrated temperature display	Alarm includes NIST calibrated display of the current interior and high/low temperature
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
-20°C capable	Low temperature capability ideal for certain sensitive items
Factory installed lock	Keyed lock for a secure interior
Adjustable thermostat	Dial thermostat located inside the unit
Removable shelves	Wire shelves can be removed to accommodate different sizes or for easy cleanup

## FS30LMED Specifications:

Overview	
Height of Cabinet	24.5" (62 cm)
Height to Hinge Cap	24.63" (63 cm)
Width	18.5" (47 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.8 cu.ft. (51 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	50.0 lbs. (23 kg)
Shipping Weight	53.0 lbs. (24 kg)
Estimated Time to Ship	3 to 5 days
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	18.63" (47 cm)
Interior Width	13.38" (34 cm)
Interior Depth	13.0" (33 cm)
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
Level Legs	2
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	13.38" (34 cm)
Compressor Step Depth	5.75" (15 cm)

