

VT65ML7CSSADA



32.25" x 23.75" x 23.5" (H x W x D)

Commercial ADA compliant built-in medical all-freezer capable of -25° C operation with stainless steel exterior and lock

Highlights:

- ETL-S listed to NSF-7 commercial standards
- 32 inch height fits under lower ADA compliant counters
- Factory installed lock provides security you can count on

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
ADA Compliant	32 inch height is designed to fit under ADA compliant counters
Factory installed lock	Keyed lock for a secure interior
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinetry
Fully finished cabinet	Allows the unit to be used freestanding
Wrapped stainless steel exterior	Durable elegance built to last
Professional towel bar handle	A curved handle in brushed stainless steel provides generous room for a comfortable grip
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	Static cooling system for improved temperature stability

VT65ML7CSSADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.75" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.5" (65 cm)
Depth with door at 90°	45.25" (115 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Weight	105.0 lbs. (48 kg)
Shipping Weight	110.0 lbs. (50 kg)
Estimated Time to Ship	2 to 4 days
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Digital
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.75" (45 cm)
Compressor Step Depth	6.0" (15 cm)

Temperature Range

