

VT65ML7SSH



33.5" x 23.63" x 23.5" (H x W x D)

Commercial freestanding medical all-freezer capable of -25° C operation, with lock, wrapped stainless steel door and horizontal handle

Highlights:

- Factory-installed lock provides security you can count on
- Stainless steel door complete with sleek horizontal handle
- 25° C operation for safe storage of temperature sensitive materials

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
Slim counter height dimensions	24" footprint allows versatile placement
Fully finished white cabinet	Allows the freezer to be used freestanding
Stainless steel door	Durable design with lasting elegance
Professional horizontal handle	Thin 14mm diameter on stainless steel handle set horizontally across the door
Factory installed lock	Keyed lock for a secure interior
-25° C capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	Static cooling system for improved temperature stability
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened

VT65ML7SSH Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.0" (117 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Shipping Weight	110.0 lbs. (50 kg)
Estimated Time to Ship	2 to 4 days
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Yes
Crisper Finish	Opaque
Crisper Cover	Glass
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.75" (45 cm)

Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C

