



BIM18SS



34.25" x 17.75" x 24" (H x W x D)

18" wide frost-free icemaker in for built-in or freestanding use, with stainless steel door and black cabinet

Highlights:

Produces and stores up to 8 lbs. of crescent ice cubes in a removable bin

Uniquely sized just under 18 inches wide for easy fit under the counter

Flexible design allows built-in or freestanding use under counters

Product Features:

Built-in capable	Make the best use of space by installing your appliance under the counter
No pump or drain required	Convenient design allows more flexibility in positioning the unit
Ice production	Makes and stores up to 8 lbs. of crescent cubes
Stainless steel door	Fully wrapped in stainless steel for a professional look
Factory installed lock	Keyed lock for a secure interior (2 keys included)
Removable bin	Bucket can be removed for fast and easy cleaning
Digital thermostat	Electronic controls for precise temperature management.
Digital display	Temperature readout can be shown in Celsius or Fahrenheit
Frost-free operation	Eliminates the need to manually defrost the interior



BIM18SS Specifications:

Overview	
Height of Cabinet	34.25" (87 cm)
Width	17.75" (45 cm)
Depth	24.0" (61 cm)
Depth with Handle	25.75" (65 cm)
Depth with door at 90°	40.0" (102 cm)
Capacity	2.7 cu.ft. (76 L)
Defrost Type	Frost-Free
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.1
Voltage/Frequency	115 V AC/60 Hz
Weight	82.0 lbs. (37 kg)
Shipping Weight	85.0 lbs. (39 kg)
Estimated Time to Ship	Out of stock; ETA 9/7/2020
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Icemaker	
Door Swing	RHD
Reversible	Yes
Daily Ice Production	8.0 lbs. (4 kg)
Ice Storage Capacity	8.0 lbs. (4 kg)
Ice Shape	Crescent
Number of Ice Cube Sizes	1
Interior Light	Yes
Fan Type	Interior and Exterior
Refrigerant Type	R134a
Refrigerant Amount	3.9 oz.
High Side PSI	270.0
Low Side PSI	103.0
Interior Height	23.5" (60 cm)
Interior Width	12.75" (32 cm)
Interior Depth	16.75" (43 cm)

Compressor Step Height	4.5" (11 cm)
Compressor Step Width	12.75" (32 cm)
Compressor Step Depth	4.5" (11 cm)
Level Legs	4
Temperature Range	-22 to 14°F

