

ACR161W



22.88" x 18.75" x 18.38" (H x W x D)

Compact healthcare all-refrigerator with self-closing solid door, front lock, digital controls, and external temperature readout

Highlights:

Designed and constructed for reliable cold storage in healthcare facilities

External temperature readout of the current and high/low temperatures

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Product Features:

| EQTemp Healthcare Refrigerator | All-refrigerator designed to operate between 2 and 8°C for a variety of storage application in medical offices and other healthcare facilities | |
|--------------------------------|--|--|
| Temperature Range: 2º to 8ºC | Preset to 5°C as recommended for many storage applications | |
| Compact size | Full 1.58 cu.ft. capacity inside conveniently slim footprint | |
| External temperature readout | Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button | |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range | |
| Buffered temperature probe | Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines | |
| Access port | 3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of user- provided monitoring equipment | |
| Factory installed lock | Keyed lock for a secure interior (2 keys included) | |
| Automatic defrost | Reduced user maintenance with automatic defrost | |

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com







ACR161W Specifications:

| Overview | |
|-------------------------------|----------------------------------|
| Height of Cabinet | 22.88" (58 cm) |
| Width | 18.75" (48 cm) |
| Width with Door Open | 19.25" (49 cm) |
| Depth | 18.38" (47 cm) |
| Depth with door at 90° | 35.63" (91 cm) |
| Capacity | 1.58 cu.ft. (45 L) |
| Defrost Type | Automatic |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 0.6 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 38.0 lbs. (17 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101082912 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Shelf Type | Wire |
| Shelf Qty | 1 |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 0.85oz. |
| High Side PSI | 1.45 |
| Low Side PSI | 0.85 |
| Level Legs Qty | 2 |
| Interior Light | Yes |
| Temperature Range | 2º to 8ºC |
| Sound Level | 36.8 dB |
| Dimensions | |
| Interior Height | 16.63" (42 cm) |
| | |
| Interior Width | 15.63" (40 cm) |
| | 15.63" (40 cm) 12.13" (31 cm) |
| Interior Width | |

| Compressor Step Width | 15.63" (40 cm) |
|-----------------------|----------------|
| Compressor Step Depth | 5.25" (13 cm) |





Front

